

Safety Data Sheet

Product :

Propane

Page :1/5

MSDS Nr : 104_AL

Version : 1.01

Date : 31/07/2002

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MSDS Nr	104_AL
Product name	Propane
Chemical formula	C3H8
Company identification	see heading and/or footer see paragraph 16 "OTHER INFORMATION"
Emergency phone numbers	see heading and/or footer see paragraph 16 "OTHER INFORMATION"

2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation	Substance.
Components/Impurities	Contains no other components or impurities which will influence the classification of the product.
CAS Nr	00074-98-6
EEC Nr (from EINECS)	200-827-9

3 HAZARDS IDENTIFICATION

Hazards identification	Liquefied gas Extremely flammable
------------------------	--------------------------------------

4 FIRST AID MEASURES

Inhalation	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Skin/eye contact	For liquid spillage - flush with water for at least 15 minutes
Ingestion	Ingestion is not considered a potential route of exposure.

5 FIRE FIGHTING MEASURES

Specific hazards	Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	Incomplete combustion may form carbon monoxide.
Suitable extinguishing media	All known extinguishants can be used.

Safety Data Sheet

Product :

Propane

Page :2/5

MSDS Nr : 104_AL

Version : 1.01

Date : 31/07/2002

Specific methods

If possible, stop flow of product.
Move away from the container and cool with water from a protected position.
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.

Special protective equipment for fire fighters

In confined space use self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Evacuate area.

Ensure adequate air ventilation.

Eliminate ignition sources.

Environmental precautions

Try to stop release.

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Clean up methods

Ventilate area.

7 HANDLING AND STORAGE

Handling and storage

Ensure equipment is adequately earthed.

Suck back of water into the container must be prevented.

Purge air from system before introducing gas.

Do not allow backfeed into the container.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Keep away from ignition sources (including static discharges).

Segregate from oxidant gases and other oxidants in store.

Refer to supplier's container handling instructions.

Keep container below 50°C in a well ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit value -TLV(ACGIH)

2500 ppm (2000 edition)

Exposure limit value for country

Germany: MAK= 1000 ppm

Personal protection

Ensure adequate ventilation.

Do not smoke while handling product.

Safety Data Sheet

Product :

Propane

Page :3/5

MSDS Nr : 104_AL

Version : 1.01

Date : 31/07/2002

9 PHYSICAL AND CHEMICAL PROPERTIES

Molecular weight	44
Melting point	-188 °C
Boiling point	-42.1 °C
Critical temperature	97 °C
Relative density, gas	1.5 (air=1)
Relative density, liquid	0.58 (water=1)
Vapour Pressure 20°C	8.3 bar
Solubility mg/l water	75 mg/l
Appearance/Colour	Colourless gas
Odour	Sweetish Poor warning properties at low concentrations. Stenchant often added
Autoignition temperature	470 °C
Flammability range	2.2-9.5 vol% in air.
Other data	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

10 STABILITY AND REACTIVITY

Stability and reactivity	Can form explosive mixture with air. May react violently with oxidants.
--------------------------	--

11 TOXICOLOGICAL INFORMATION

General	No known toxicological effects from this product.
---------	---

12 ECOLOGICAL INFORMATION

General	No known ecological damage caused by this product.
---------	--

13 DISPOSAL CONSIDERATIONS

General	Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required.
---------	--

Safety Data Sheet

Product :

Propane

Page :4/5

MSDS Nr : 104_AL

Version : 1.01

Date : 31/07/2002

14 TRANSPORT INFORMATION

Proper shipping name	Propane
UN Nr	1978
Class/Div	2.1
ADR/RID Classification code	2, 2°F
ADR/RID Hazard Nr	23
Labelling ADR	Label 3: flammable gas
Other transport information	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured and: - cylinder valve is closed and not leaking - valve outlet cap nut or plug (where provided) is correctly fitted - valve protection device (where provided) is correctly fitted - there is adequate ventilation. - compliance with applicable regulations.

15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548	601-003-00-5.
EC Classification	F+;R12
-Symbols	F+: Extremely flammable
-Risk phrases	R12 Extremely flammable.
-Safety phrases	S9 Keep container in well ventilated place. S16 Keep away from ignition sources - No smoking.

16 OTHER INFORMATION

Ensure all national/local regulations are observed.

Ensure operators understand the flammability hazard.

Contact with liquid may cause cold burns/frost bite.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

Safety Data Sheet

Product :

Propane

Page :5/5

MSDS Nr : 104_AL

Version : 1.01

Date : 31/07/2002

This MSDS is for information purposes only and is subject to change without notice. [Prior to purchase of products, please contact your local Air Liquide office for a complete MSDS (with Manufacturer's name and emergency phone number).]

End of document.

Number of pages :5